

Modeling and Numerical Simulations of Magnetic Field Generation in a Plasma due to Anisotropic Laser Heating

Afeintou SANGAM

¹Mathématiques Appliquées de Bordeaux Laboratory
Université Bordeaux 1, FRANCE

²Centre Lasers Intenses et Applications Laboratory
Université Bordeaux 1, FRANCE

Cargèse, August 10th, 2006

PHD Student in Applied Mathematics and Scientific Computing

PHD supervisors

Pr. Bruno DUBROCA, MAB and CELIA
Université Bordeaux 1

Pr. Pierre CHARRIER, MAB and CELIA
Université Bordeaux 1

In collaboration with

Dr. Jean-Pierre MORREEUW, CEA-CESTA Barp

Pr. Vladmir TIKHONCHUK, CELIA
Université Bordeaux 1

Outline

Context


Model

Numerical approximation

Numerical tests

Conclusion and perspectives


- **Inertiel Confinement Fusion (ICF).**



- Framework: **Laser-Plasma interaction.**

- Laser intensity $I = 3 \times 10^{15} - 10^{16} \text{ W/cm}^2$
- Plasma temperature $T_e = 1 - 2 \text{ keV} = 1.2 - 2.3 \times 10^7 \text{ °K}$
- Typical time 50–100ps

Context



A mechanism to generate Magnetic Field

Faraday's Law F. L.

$$\partial_t \mathbf{B} = -\nabla \times \mathbf{E}_{\text{elec}}$$

A mechanism to generate Magnetic Field

Faraday's Law F. L.

$$\partial_t \mathbf{B} = -\nabla \times \mathbf{E}_{\text{elec}}$$

Generalized Ohm's Law G. O. L.

$$\begin{aligned} \mathbf{E}_{\text{elec}} = & -\mathbf{u}_e \times \mathbf{B} - \nabla W / (2e) \\ & - (\nabla \cdot (n_e \mathbf{U})) / (n_e e) + \mathbf{R}_{ie} / (n_e e) \end{aligned}$$

A mechanism to generate Magnetic Field

Faraday's Law F. L.

$$\partial_t \mathbf{B} = -\nabla \times \mathbf{E}_{\text{elec}}$$

Generalized Ohm's Law G. O. L.

$$\begin{aligned} \mathbf{E}_{\text{elec}} = & -\mathbf{u}_e \times \mathbf{B} - \nabla W / (2e) \\ & - (\nabla \cdot (n_e \mathbf{U})) / (n_e e) + \mathbf{R}_{ie} / (n_e e) \end{aligned}$$

Magnetic Field Evolution Equation

$$\begin{aligned} \partial_t \mathbf{B} - \nabla \times (\mathbf{V} \times \mathbf{B}) - \mu_0^{-1} \nabla \times (\sigma_0^{-1} \nabla \times \mathbf{B}) \\ = \nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U})) \end{aligned}$$

A mechanism to generate Magnetic Field

Faraday's Law F. L.

$$\partial_t \mathbf{B} = -\nabla \times \mathbf{E}_{\text{elec}}$$

Generalized Ohm's Law G. O. L.

$$\begin{aligned} \mathbf{E}_{\text{elec}} = & -\mathbf{u}_e \times \mathbf{B} - \nabla W / (2e) \\ & - (\nabla \cdot (n_e \mathbf{U})) / (n_e e) + \mathbf{R}_{ie} / (n_e e) \end{aligned}$$

Magnetic Field Evolution Equation

$$\begin{aligned} \partial_t \mathbf{B} - \nabla \times (\mathbf{V} \times \mathbf{B}) - \mu_0^{-1} \nabla \times (\sigma_0^{-1} \nabla \times \mathbf{B}) \\ = \nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U})) \end{aligned}$$

Source term

$$\nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = 0 \implies \mathbf{B} = \text{constante}$$

A mechanism to generate Magnetic Field

Faraday's Law F. L.

$$\partial_t \mathbf{B} = -\nabla \times \mathbf{E}_{\text{elec}}$$

Generalized Ohm's Law G. O. L.

$$\begin{aligned} \mathbf{E}_{\text{elec}} = & -\mathbf{u}_e \times \mathbf{B} - \nabla W / (2e) \\ & - (\nabla \cdot (n_e \mathbf{U})) / (n_e e) + \mathbf{R}_{ie} / (n_e e) \end{aligned}$$

Magnetic Field Evolution Equation

$$\begin{aligned} \partial_t \mathbf{B} - \nabla \times (\mathbf{V} \times \mathbf{B}) - \mu_0^{-1} \nabla \times (\sigma_0^{-1} \nabla \times \mathbf{B}) \\ = \nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U})) \end{aligned}$$

Source term

$$\nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = 0 \implies \mathbf{B} = \text{constante}$$

Source term

- $$\nabla \times ((n_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = \nabla \times (\mathbf{U} \cdot \nabla \ln n_e) + \nabla \times (\nabla \cdot (\mathbf{U} - U\mathbf{I}))$$

Source term

- $$\nabla \times ((n_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = \nabla \times (\mathbf{U} \cdot \nabla \ln n_e) + \nabla \times (\nabla \cdot (\mathbf{U} - U\mathbf{I}))$$
- $\nabla \times (\mathbf{U} \cdot \nabla \ln n_e) \& \nabla \rho \times \nabla T_e = 0$ for times $\ll 100\text{ps}$ and isotropic initial conditions

Source term

- $\nabla \times ((n_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = \nabla \times (\mathbf{U} \cdot \nabla \ln n_e) + \nabla \times (\nabla \cdot (\mathbf{U} - \mathbf{UI}))$
- $\nabla \times (\mathbf{U} \cdot \nabla \ln n_e) \& \nabla \rho \times \nabla T_e = 0$ for times $\ll 100\text{ps}$ and isotropic initial conditions
- $\nabla \times (\nabla \cdot (\mathbf{U} - \mathbf{UI})) \neq 0$ if \mathbf{U} is **anisotropic** tensor

The model

Source term

- $\nabla \times ((n_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = \nabla \times (\mathbf{U} \cdot \nabla \ln n_e) + \nabla \times (\nabla \cdot (\mathbf{U} - \mathbf{UI}))$
- $\nabla \times (\mathbf{U} \cdot \nabla \ln n_e) \& \nabla \rho \times \nabla T_e = 0$ for times $\ll 100\text{ps}$ and isotropic initial conditions
- $\nabla \times (\nabla \cdot (\mathbf{U} - \mathbf{UI})) \neq 0$ if \mathbf{U} is **anisotropic** tensor

Source term

Ten-moments approximation takes into account the anisotropy of electron pressure

The model

Source term

- $\nabla \times ((n_e)^{-1} \nabla \cdot (n_e \mathbf{U})) = \nabla \times (\mathbf{U} \cdot \nabla \ln n_e) + \nabla \times (\nabla \cdot (\mathbf{U} - \mathbf{UI}))$
- $\nabla \times (\mathbf{U} \cdot \nabla \ln n_e) \& \nabla \rho \times \nabla T_e = 0$ for times $\ll 100\text{ps}$ and isotropic initial conditions
- $\nabla \times (\nabla \cdot (\mathbf{U} - \mathbf{UI})) \neq 0$ if \mathbf{U} is **anisotropic** tensor

Source term

Ten-moments approximation takes into account the anisotropy of electron pressure

Ten-moments approximation: derivation procedure

Ten-moments approximation: derivation procedure

- Electrons Kinetic equation
 - in the high frequency laser field
 - in presence of the quasi-static electric field \mathbf{E}_{elec}
 - and magnetic field \mathbf{B}

Ten-moments approximation: derivation procedure

- Electrons Kinetic equation
in the high frequency laser field
in presence of the quasi-static electric field \mathbf{E}_{elec}
and magnetic field \mathbf{B}
- Average this equation over laser period
Laser's contribution contained in the tensor

$$\mathbf{W} = \varepsilon_0 \langle \mathbf{E}_L \otimes \mathbf{E}_L \rangle / n_c$$

where \mathbf{E}_L is the laser electric field
 n_c is the critical density

Ten-moments approximation: derivation procedure

- Electrons Kinetic equation
in the high frequency laser field
in presence of the quasi-static electric field \mathbf{E}_{elec}
and magnetic field \mathbf{B}

- Average this equation over laser period
Laser's contribution contained in the tensor

$$\mathbf{W} = \varepsilon_0 \langle \mathbf{E}_L \otimes \mathbf{E}_L \rangle / n_c$$

where \mathbf{E}_L is the laser electric field
 n_c is the critical density

- Take the consecutive moments over the electron distribution function f
assume the quasi-neutrality of the plasma

Ten-moments approximation: Notations and equations

- | | | |
|--------------------|---|--|
| n_e | = | $\int f \, dv$ |
| $n_e \mathbf{u}_e$ | = | $\int f \mathbf{v} \, dv$ |
| \mathbf{P} | = | $\int f (\mathbf{v} - \mathbf{u}_e) \otimes (\mathbf{v} - \mathbf{u}_e) \, dv$ |
| \mathbf{U} | = | $\mathbf{P} / n_e - \mathbf{W}$ |
| \mathbf{V} | = | $\mathbf{u}_e + \mathbf{j} / (n_e e) \simeq \mathbf{u}_e$ |
| \mathbf{E} | = | $\rho \mathbf{V} \otimes \mathbf{V} + n_e \mathbf{U}$ |
-

$$\partial_t \rho + \nabla \cdot (\rho \mathbf{V}) = 0$$

$$\partial_t (\rho \mathbf{V}) + \nabla \cdot \mathbf{E} = -n_e \nabla W / 2$$

$$\begin{aligned} \partial_t \mathbf{E} + \nabla \cdot (\rho \mathbf{H} \otimes \mathbf{V})^S + \nabla \cdot \mathbf{Q} &= -n_e (\nabla W \otimes \mathbf{V})^S \\ &+ 2\nu_T n_e \mathbf{W} + \mathbf{S}_{BU} - \mathbf{S}_I - \mathbf{S}_B \end{aligned}$$

Ten-moments approximation to Euler system

-

$$\begin{aligned} \partial_t \mathbf{E} + \nabla \cdot (\rho \mathbf{H} \otimes \mathbf{V})^S + \nabla \cdot \mathbf{Q} = -n_e (\nabla W \otimes \mathbf{V})^S \\ + 2\nu_T n_e \mathbf{W} + \mathbf{S}_{BU} - \nu_P (\mathbf{P} - P\mathbf{I}) - \mathbf{S}_B \end{aligned} \quad (1)$$

- Set $\mathbf{B} = 0$ and $\mathbf{W} = 0$
- Tend $\nu_P \rightarrow +\infty$ and make expansion of (1) respect to ν_P
 $\implies \mathbf{P} = P\mathbf{I}$
- Take $\frac{1}{2}$ trace of the result
- Set $E = \rho(\mathbf{V}_1^2 + \mathbf{V}_2^2)/2 + 3n_e U/2$ and $p = n_e U$
- Euler energy equation

$$\partial_t E + \nabla \cdot ((E + p)\mathbf{V}) = 0$$

Equations of the model: EMHD model

$$\begin{aligned}\partial_t \mathbf{B} + \nabla \cdot (\mathbf{B}(\mathbf{V} + \mathbf{V}_N + \mathbf{V}_H)) - \mu_0^{-1} \nabla \times (\sigma_0^{-1} \nabla \times \mathbf{B}) \\ = \nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U}))\end{aligned}$$

$$\partial_t \rho + \nabla \cdot (\rho \mathbf{V}) = 0$$

$$\partial_t (\rho \mathbf{V}) + \nabla \cdot \mathbf{E} = -n_e \nabla W / 2$$

$$\begin{aligned}\partial_t \mathbf{E} + \nabla \cdot (\rho \mathbf{H} \otimes \mathbf{V})^S + \nabla \cdot \mathbf{Q} = -n_e (\nabla W \otimes \mathbf{V})^S \\ + 2\nu_T n_e \mathbf{W} + \mathbf{S}_{BU} - \mathbf{S}_I - \mathbf{S}_B\end{aligned}$$



B. Dubroca *et al.*, *Physics of Plasmas*, **11**, 3830 (2004)



Work in preparation

Model: closure relations

Unknowns of the model

B , ρ , \mathbf{V} , \mathbf{U} and Q

In 2D geometry

number of unknowns = 17

number of equations = 8



Crucial necessity
to close the model

Model: closure relations

Unknowns of the model

B , ρ , \mathbf{V} , \mathbf{U} and \mathbf{Q}

In 2D geometry

number of unknowns = 17

number of equations = 8



Crucial necessity
to close the model

Closure relations

On electronic pressure $\mathbf{P} = k_B \mathbf{T}_e = \mathbf{U} + \mathbf{W}$

On heat flux tensor $\mathbf{Q} = \mathbf{Q}_{\text{iso}} + \mathbf{Q}_{\text{ani}}$

where $\mathbf{Q}_{\text{iso}} = -6(\kappa \nabla U \otimes \mathbf{I})^S / 5$

$\mathbf{Q}_{\text{ani}} = -4\delta k_B T (\nabla \otimes \mathbf{\Pi})^S / (5n_e m_e \nu_{ie})$

with $\mathbf{\Pi} = (\mathbf{U} - \mathbf{U}\mathbf{I})$

Input parameters for simulations

Laser

Laser intensity $I = 3 \times 10^{15} \text{ W/cm}^2$

Radius of the speckle $R = 10 \mu\text{m}$


Laser wavelength $\lambda_0 = 0.35 \mu\text{m}$

Plasma

Electronic Density $n_e = 9 \times 10^{21} \text{ cm}^{-3}$

Plasma temperature $T_e = 2.3 \times 10^7 \text{ K}$

Structure of generated magnetic field after 50 ps



Definition

The set of the physically admissible states of the above model is

$$\mathcal{E}_{pas} = \left\{ \mathcal{U} = (\rho \ \rho \mathbf{V} \ \mathbf{E} \ B)^t / \rho \geq 0, \right. \\ \left. \text{and } \Xi = \mathbf{E} - \rho \mathbf{V} \otimes \mathbf{V} \text{ verifies } (\Xi \xi, \xi) \geq 0 \ \forall \xi \right\}$$

Proposition

\mathcal{E}_{pas} is a **close cone and convex**



C. D. Levermore *et al.*, *SIAM J. of Appl. Math.*, **59**, **1**, 72 (1996)

Compact form

$$\begin{aligned}\partial_t \mathcal{U} + \partial_x \mathcal{F}_x(\mathcal{U}) + \partial_y \mathcal{F}_y(\mathcal{U}) + \mathcal{G}(\mathcal{U}, \partial_{xx}^2 \mathcal{U}, \partial_{yy}^2 \mathcal{U}, \partial_{xy}^2 \mathcal{U}) \\ = \mathcal{S}(\mathcal{U}) + \mathcal{R}(\mathcal{U}) + \mathcal{C}(\mathcal{U})\end{aligned}$$

Model properties

Compact form

$$\partial_t \mathcal{U} + \partial_x \mathcal{F}_x(\mathcal{U}) + \partial_y \mathcal{F}_y(\mathcal{U}) + \mathcal{G}(\mathcal{U}, \partial_{xx}^2 \mathcal{U}, \partial_{yy}^2 \mathcal{U}, \partial_{xy}^2 \mathcal{U}) \\ = \mathcal{S}(\mathcal{U}) + \mathcal{R}(\mathcal{U}) + \mathcal{C}(\mathcal{U})$$

Parabolicity

black + *magenta* = Parabolic

Problem ill-posed without the terms \mathbf{S}_{BU} , \mathbf{Q}_{ani}

Anisotropic filamentation instability

Model properties

Compact form

$$\partial_t \mathcal{U} + \partial_x \mathcal{F}_x(\mathcal{U}) + \partial_y \mathcal{F}_y(\mathcal{U}) + \mathcal{G}(\mathcal{U}, \partial_{xx}^2 \mathcal{U}, \partial_{yy}^2 \mathcal{U}, \partial_{xy}^2 \mathcal{U}) \\ = \mathcal{S}(\mathcal{U}) + \mathcal{R}(\mathcal{U}) + \mathcal{C}(\mathcal{U})$$

Parabolicity

black + *magenta* = Parabolic

Problem ill-posed without the terms \mathbf{S}_{BU} , \mathbf{Q}_{ani}


Anisotropic filamentation instability

Hyperbolicity

black + *violet* = Hyperbolic

Model properties

Hyperbolicity: waves



Hyperbolicity: waves nature

$\mathbf{V} \cdot \mathbf{n} \pm c$ *genuinely nonlinear*

$\mathbf{V} \cdot \mathbf{n}, \mathbf{V} \cdot \mathbf{n} \pm c/\sqrt{3}$ *linearly degenerated*

Approximation in time

Non-linear implicit scheme designed on
A Newton-Krylov method
Using a non-linear GMRES

Numerical approximation: main ideas

Approximation in time

Non-linear implicit scheme designed on
A Newton-Krylov method
Using a non-linear GMRES

Approximation in space

Approximate Riemann solver HLLC for Hyperbolic part
Second order accuracy extension by slope limiters (MUSCL)
Centred schemes for diffusion terms

Numerical approximation: main ideas

Approximation in time

Non-linear implicit scheme designed on
A Newton-Krylov method
Using a non-linear GMRES

Approximation in space

Approximate Riemann solver HLLC for Hyperbolic part
Second order accuracy extension by slope limiters (MUSCL)
Centred schemes for diffusion terms

Mesh

Cartesian uniform mesh in 2D

Numerical approximation: Precisely

Continuous compact form

$$\begin{aligned} \partial_t \mathcal{U} + \partial_x \mathcal{F}_x(\mathcal{U}) + \partial_y \mathcal{F}_y(\mathcal{U}) + \mathcal{G}(\mathcal{U}, \partial_{xx}^2 \mathcal{U}, \partial_{yy}^2 \mathcal{U}, \partial_{xy}^2 \mathcal{U}) \\ = \mathcal{S}(\mathcal{U}) + \mathcal{R}(\mathcal{U}) + \mathcal{C}(\mathcal{U}) = \mathcal{RHS}(\mathcal{U}(t)) \end{aligned}$$

Numerical approximation: Precisely

Continuous compact form

$$\partial_t \mathcal{U} + \partial_x \mathcal{F}_x(\mathcal{U}) + \partial_y \mathcal{F}_y(\mathcal{U}) + \mathcal{G}(\mathcal{U}, \partial_{xx}^2 \mathcal{U}, \partial_{yy}^2 \mathcal{U}, \partial_{xy}^2 \mathcal{U}) \\ = \mathcal{S}(\mathcal{U}) + \mathcal{R}(\mathcal{U}) + \mathcal{C}(\mathcal{U}) = \mathcal{RHS}(\mathcal{U}(t))$$

Discrete compact form in the cell l, m

$$\partial_t \mathcal{U}_{l,m}(t) + \frac{\mathcal{F}_{l+1/2,m}(t) - \mathcal{F}_{l-1/2,m}(t)}{\Delta x} \\ \frac{\mathcal{F}_{l,m+1/2}(t) - \mathcal{F}_{l,m-1/2}(t)}{\Delta y} + \mathcal{G}_{l,m}(\mathcal{U}(t)) = \mathcal{RHS}_{l,m}(\mathcal{U}(t))$$

Numerical approximation: Implicit method

Non-linear equation

Discrete compact form in the cell l, m re-written as

$$\partial_t \mathcal{U}_{l,m}(t) = \Theta_{l,m}(\mathcal{U}(t))$$

Implicit Euler method time discretisation

$$\mathcal{U}_{l,m}^{n+1} - \mathcal{U}_{l,m}^n - \Delta t \Theta(\mathcal{U}^{n+1}) = 0$$

Non-linear equation follows

$$\mathbf{F}(\mathcal{U}^{n+1}) = 0$$

That must be solved to obtain \mathcal{U}^{n+1}

Numerical approximation: Implicit method

Newton method to solve Non-linear equation

Numerical approximation: Implicit method

Newton method to solve Non-linear equation

- At each time solve $\mathbf{F}(\mathcal{U}) = 0$ by a Newton method
 \implies linear system

$$\mathcal{A}(\mathcal{U}^k)(\mathcal{U}^{k+1} - \mathcal{U}^k) = -\mathbf{F}(\mathcal{U}^k)$$

where $\mathcal{A}(\mathcal{U}^k) = \mathbf{F}'(\mathcal{U}^k)$

Newton method to solve Non-linear equation

- At each time solve $\mathbf{F}(\mathcal{U}) = 0$ by a Newton method
 \implies linear system

$$\mathcal{A}(\mathcal{U}^k)(\mathcal{U}^{k+1} - \mathcal{U}^k) = -\mathbf{F}(\mathcal{U}^k)$$

where $\mathcal{A}(\mathcal{U}^k) = \mathbf{F}'(\mathcal{U}^k)$

- Non-linear GMRES coupled to JFNK method
JFNK = Jacobian Free Newton Krylov

Newton method to solve Non-linear equation

- At each time solve $\mathbf{F}(\mathcal{U}) = 0$ by a Newton method
 \implies linear system

$$\mathcal{A}(\mathcal{U}^k)(\mathcal{U}^{k+1} - \mathcal{U}^k) = -\mathbf{F}(\mathcal{U}^k)$$

where $\mathcal{A}(\mathcal{U}^k) = \mathbf{F}'(\mathcal{U}^k)$

- Non-linear GMRES coupled to JFNK method
JFNK = Jacobian Free Newton Krylov
 - No explicit storage of jacobian matrix \mathcal{A}

Newton method to solve Non-linear equation

- At each time solve $\mathbf{F}(\mathcal{U}) = 0$ by a Newton method
 \implies linear system

$$\mathcal{A}(\mathcal{U}^k)(\mathcal{U}^{k+1} - \mathcal{U}^k) = -\mathbf{F}(\mathcal{U}^k)$$

where $\mathcal{A}(\mathcal{U}^k) = \mathbf{F}'(\mathcal{U}^k)$

- Non-linear GMRES coupled to JFNK method
JFNK = Jacobian Free Newton Krylov
 - No explicit storage of jacobian matrix \mathcal{A}
 - Know how to compute the matrix-vector product $\mathcal{A}z$

Newton method to solve Non-linear equation

- At each time solve $\mathbf{F}(\mathcal{U}) = 0$ by a Newton method
 \implies linear system

$$\mathcal{A}(\mathcal{U}^k)(\mathcal{U}^{k+1} - \mathcal{U}^k) = -\mathbf{F}(\mathcal{U}^k)$$

where $\mathcal{A}(\mathcal{U}^k) = \mathbf{F}'(\mathcal{U}^k)$

- Non-linear GMRES coupled to JFNK method
JFNK = Jacobian Free Newton Krylov
 - No explicit storage of jacobian matrix \mathcal{A}
 - Know how to compute the matrix-vector product $\mathcal{A}\mathbf{z}$

- finite difference to compute $\mathcal{A}\mathbf{z}$

$$\mathcal{A}\mathbf{z} = \mathcal{A}(\mathcal{U}^k)\mathbf{z} = \frac{\mathbf{F}(\mathcal{U}^k + \varepsilon\mathbf{z}) - \mathbf{F}(\mathcal{U}^k)}{\varepsilon} \text{ with } \varepsilon = O(\varepsilon_{\text{machine}}^{1/2})$$

Newton method to solve Non-linear equation

- At each time solve $\mathbf{F}(\mathcal{U}) = 0$ by a Newton method
 \implies linear system

$$\mathcal{A}(\mathcal{U}^k)(\mathcal{U}^{k+1} - \mathcal{U}^k) = -\mathbf{F}(\mathcal{U}^k)$$

where $\mathcal{A}(\mathcal{U}^k) = \mathbf{F}'(\mathcal{U}^k)$

- Non-linear GMRES coupled to JFNK method
JFNK = Jacobian Free Newton Krylov
 - No explicit storage of jacobian matrix \mathcal{A}
 - Know how to compute the matrix-vector product $\mathcal{A}\mathbf{z}$

- finite difference to compute $\mathcal{A}\mathbf{z}$

$$\mathcal{A}\mathbf{z} = \mathcal{A}(\mathcal{U}^k)\mathbf{z} = \frac{\mathbf{F}(\mathcal{U}^k + \varepsilon\mathbf{z}) - \mathbf{F}(\mathcal{U}^k)}{\varepsilon} \text{ with } \varepsilon = O(\varepsilon_{\text{machine}}^{1/2})$$

- For one fixed ε , use preconditioners

Numerical approximation: function $\mathbf{F}(\mathcal{U})$

Discrete compact form in the cell l, m

$$\partial_t \mathcal{U}_{l,m}(t) + \frac{\mathcal{F}_{l+1/2,m}(t) - \mathcal{F}_{l-1/2,m}(t)}{\Delta x} + \frac{\mathcal{F}_{l,m+1/2}(t) - \mathcal{F}_{l,m-1/2}(t)}{\Delta y} + \mathcal{G}_{l,m}(\mathcal{U}(t)) = \mathcal{RHS}_{l,m}(\mathcal{U}(t))$$

Numerical approximation: $\mathbf{F}(\mathcal{U})$

$\mathcal{F}_{l\pm 1/2,m}(t)$ and $\mathcal{F}_{l,m\pm 1/2}(t)$

Finite volume method

Numerical approximation: $\mathbf{F}(\mathcal{U})$

$$\mathcal{F}_{l\pm 1/2,m}(t) \text{ and } \mathcal{F}_{l,m\pm 1/2}(t)$$

Finite volume method

- 1D Riemann problem by coordinate interface

Numerical approximation: $\mathbf{F}(\mathcal{U})$

$$\mathcal{F}_{l\pm 1/2,m}(t) \text{ and } \mathcal{F}_{l,m\pm 1/2}(t)$$

Finite volume method

- 1D Riemann problem by coordinate interface
- Approximate Riemann solver HLLC for ten-moments

Numerical approximation: $\mathbf{F}(\mathcal{U})$

$\mathcal{F}_{l\pm 1/2,m}(t)$ and $\mathcal{F}_{l,m\pm 1/2}(t)$

Finite volume method

- 1D Riemann problem by coordinate interface
- Approximate Riemann solver HLLC for ten-moments

HLLC for ten-moments properties


Positively conservative

Exact resolution of 1-shock and 5-shock

Exact resolution of contact discontinuity

HLLC solver: contact discontinuity


	ρ	\mathbf{V}_1	\mathbf{V}_2	\mathbf{P}_{11}	\mathbf{P}_{12}	\mathbf{P}_{22}	\mathbf{P}_{33}
left state	1	0	3	2	0	2	2
right state	0.1	0	3	2	0	2	2



Stationary contact discontinuity problem at $t = 0.2$, 100 cells on $(-0.5, 0.5)$ and $CFL = 0.5$

HLLC solver: Sod's shock tube problem

	ρ	\mathbf{V}_1	\mathbf{V}_2	\mathbf{P}_{11}	\mathbf{P}_{12}	\mathbf{P}_{22}	\mathbf{P}_{33}
left state	1	0	0	10^5	0	10^5	10^5
right state	0.125	0	0	10^4	0	10^4	10^4



Sod's shock tube problem at $t = 0.1$, 100 cells on $(-0.5, 0.5)$ and $CFL = 0.5$

Magnetic field generation: feedbacks neglected

$$\begin{aligned}\partial_t \mathbf{B} + \nabla \cdot (\mathbf{B} \mathbf{V}_{\text{mag}}) - \mu_0^{-1} \nabla \times (\sigma_0^{-1} \nabla \times \mathbf{B}) \\ = \nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U}))\end{aligned}$$

$$\partial_t \rho + \nabla \cdot (\rho \mathbf{V}) = 0$$

$$\partial_t (\rho \mathbf{V}) + \nabla \cdot \mathbf{E} = -n_e \nabla W / 2$$

$$\begin{aligned}\partial_t \mathbf{E} + \nabla \cdot (\rho \mathbf{H} \otimes \mathbf{V})^S + \nabla \cdot \mathbf{Q}_{\text{iso}} = -n_e (\nabla W \otimes \mathbf{V})^S \\ + 2\nu_T n_e \mathbf{W} - \mathbf{S}_I\end{aligned}$$

Movie on magnetic field generation: feedbacks neglected

Laser	$I = 3 \times 10^{15} \text{ W/cm}^2$
	$R = 10 \mu\text{m}$
	$\lambda_0 = 0.35 \mu\text{m}$
Plasma	$n_e = 9 \times 10^{21} \text{ cm}^{-3}$
	$T_e = 2.3 \times 10^7 \text{ }^\circ\text{K}$

Magnetic field generation: feedbacks accounted for

$$\partial_t \mathbf{B} - \mu_0^{-1} \nabla \times (\sigma_0^{-1} \nabla \times \mathbf{B}) = \nabla \times ((en_e)^{-1} \nabla \cdot (n_e \mathbf{U}))$$


$$\partial_t \rho = 0$$

$$\partial_t (\rho \mathbf{V}) = 0$$

$$\partial_t \mathbf{E} + \nabla \cdot \mathbf{Q}_{\text{iso}} = 2\nu_T n_e \mathbf{W} - \mathbf{S}_I - \mathbf{S}_B$$

where $\mathbf{S}_B = 2n_e e (\mathbf{U} \times \mathbf{B})^S / m_e$ is the rotation of \mathbf{U}

Magnetic field structure: feedbacks accounted for



Magnetic field develops small scale perturbations, this is an anisotropic filamentation-type instability, after 17 ps. The computation cell length is 1 μm

Numerical tests

Instability analysis: \mathbf{U} splitting

$$\mathbf{U} = \mathbf{\Lambda} + \mathbf{\Pi}$$

where

$$\mathbf{\Lambda} = \begin{bmatrix} U & 0 & 0 \\ 0 & U & 0 \\ 0 & 0 & U \end{bmatrix}, \quad \mathbf{\Pi} = \begin{bmatrix} \Pi_{\perp} & \Pi_{\wedge} & 0 \\ \Pi_{\wedge} & -\Pi_{\perp} & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Adequate form for reduced model

$$\begin{aligned} \partial_t B - \eta(\partial_x^2 + \partial_y^2)B &= \frac{1}{e}(\partial_x^2 - \partial_y^2)\Pi_{\wedge} - \frac{2}{e}\partial_{xy}^2\Pi_{\perp} \\ \partial_t \Pi_{\perp} &= -\nu_P \Pi_{\perp} + (\nu_T - \frac{1}{2}\nu_P)W - \frac{2e}{m_e}\Pi_{\wedge}B \\ \partial_t \Pi_{\wedge} &= -\nu_P \Pi_{\wedge} + \frac{2e}{m_e}\Pi_{\perp}B \end{aligned}$$

Instability analysis

- Wave form for analysis $\mathcal{A} \exp(\omega t) \cos(\mathbf{k}_x x + \mathbf{k}_y y)$
- Dispersion relation
$$(\omega + \nu_p)(\omega + \eta|\mathbf{k}|^2) = -\left(\frac{2\nu_T}{\nu_p} - 1\right)\frac{W}{m_e}|\mathbf{k}|^2 \cos 2\theta$$
- Asymptotically $\omega \sim |\mathbf{k}|^2$
 \implies grid size is unstable

Instability analysis: stabilisation

- Following terms stabilize the model

$$\mathbf{S}_{BU} = 2\delta_{visc} U (\nabla \otimes (\nabla \times \mathbf{B}))^S / (\epsilon \mu_0)$$

$$\mathbf{Q}_{ani} = -4\delta k_B T_e (\nabla \otimes \mathbf{\Pi})^S / (5n_e m_e \nu_{ie})$$


- New dispersion relation follows:

$$(\omega + \nu_p + \delta \kappa |\mathbf{k}|^2)(\omega + \eta |\mathbf{k}|^2) = \left[\left(\frac{2\nu_T}{\nu_P} - 1 \right) \frac{W}{m_e} - \delta_{visc} \frac{U}{m_e} \frac{c^2}{\omega_{Pe}^2} |\mathbf{k}|^2 \right] k^2$$

- Asymptotically $\omega \sim |\mathbf{k}|^2 - |\mathbf{k}|^4$

⇒ **cutoff** that must be respected by the mesh size

Magnetic field structure: feedbacks accounted for, stabilisation





Comparison maximum growth rate of magnetic field between kinetic theory, theoretical formula and Code. The computation cell length is $0.2 \mu\text{m}$. $|\mathbf{k}| = 2\pi/\lambda$



A. Bendib *et al.*, *Physical Review E.*, **55**, 7522 (1997)

Magnetic field structure: feedbacks accounted for, stabilisation



Magnetic field structure after 50 ps and the corresponding maximum growth rate. The computation cell length is 0.2 μm

Conclusion and Perspectives

Conclusion

- Obtaining of a model EMHD capable of predicting and of reproducing the generation of auto-generated magnetic fields
- Validation
 - we reproduce the analytical solutions
- Complicated and complex problem
 - equations are stiff and can be unstable \implies need of robust schemes in time and in space

Perspectives

- Study mathematically the stability of the model problem with abstract theory of PDE
- Improve the closure on heat fluxes
- Introduce the equation of laser propagation