

Multiscale modeling and control of production flows

Dieter Armbruster
Department of Mathematics,
Arizona State University
& Department of Mechanical Engineering
Eindhoven University of Technology
E-mail: armbruster@asu.edu

August 9, 2006

Collaborators

Christian Ringhofer, Mathematics ASU

Karl Kempf, Decision Science Intel

Pierre Degond, Mathematics Toulouse

Tae-Chang Jo, now Inha University South Korea

Dan Marthaler, now Northrop Grumman Aerospace Corporation

Erjen Lefeber, Systems Engineering, Eindhoven Technical
University

Partial support by NSF grants DMS 0204543 and from Intel
Corporation is gratefully acknowledged

Overview:

1. Introduction
 - ▶ Fundamental Scale of the Problem
 - ▶ Queueing theory models
 - ▶ Discrete event simulations
2. Adiabatic (quasi-static) models
 - ▶ validation against χ simulations
3. Advection diffusion equations
 - ▶ validation against factory data
 - ▶ validation against χ simulations
4. Factory Master equations for a linear factory
 - ▶ Moment expansions
 - ▶ Deriving the state equation from first principles
5. Boundary control of hyperbolic nonlinear wave equations

1) Introduction

Example: Chip production in semiconductor manufacturing.
Factory investment several billions of \$\$.

Issues:

- 1.) Hardware: how many machines, topology of production flow
- 2.) Software: starts policies, dispatch policies, production mix

a) Fundamental Scale of the Problem:

250 production stages

individual wafers or batches of a few wafers go through a machine
cycle time in a machine: from a few minutes to several hours

raw cycle time through the factory: 18 days

actual cycle time through the factory: 40 - 60 days

Stochasticity in the cycle time:

- ▶ in the machine - very little
- ▶ due to the physical process in the machine - rework - somewhat significant
- ▶ due to operators and operator availability - significant
- ▶ due to machine failure - major

b) Queueing theory models:

Each process in a machine is modelled as a queue;

stochastic arrival process into a buffer

stochastic exit process describing the machine and operator unit

Problem:

- ▶ Some processes are not modelled well using queueing models
-e.g crowding effect, operator fatigue etc.
- ▶ queueing theory not developed for non-stationary behavior

c) Simulation of choice:

Generate a faithful representation of the factory and do simulation experiments using *Discrete Event Simulations*, e.g. χ (TU Eindhoven)

Simulation of production flows with stochastic demand and stochastic production processes requires Monte Carlo Simulations

It is not scalable.

Intermediate Scale: Fluid Models

Model production flow for each production step as an ODE.

Length of the queue (buffer) in front of the step is the dependent variable

Outflux - constant mean production rate of the machine for this step.

Link: Mass conservation:

$$\frac{dx}{dt} = \textit{influx} - \textit{outflux}$$

Note: continuum in products.

Problems:

- ▶ 250 ODEs to parametrize
- ▶ how to model the delay

2) Continuum Models of production flows

Fundamental Idea:

Model high volume, many stages, production via a continuum.

Basic variable:

product density (mass density) $\rho(\mathbf{x}, \mathbf{t})$.

x - is the position in the production process, $x \in [0, 1]$.- degree of completion- stage of production

Note: For a re-entrant process a machine corresponds to many positions x .

Mass conservation and state equations

Quasi-stationary model (adiabatic model): Mass conservation and state equation

$$\begin{aligned}\frac{\partial \rho}{\partial t} + \frac{\partial F}{\partial x} &= 0 \\ F &= \rho v_{eq}\end{aligned}$$

Typical models for the equilibrium velocity v_{eq} (state equation) are

$$v_{LW}(\rho) = v_0 \left(1 - \frac{\rho}{\rho_c}\right), \quad (1)$$

$$v_Q(\rho) = \frac{v_0}{1 + \frac{L(\rho)}{L_c}}, \quad (2)$$

$$v_{eq}(\rho) = \Phi(L), \quad (3)$$

with L the total load (Work in progress, WIP) given as

$$L(\rho) = \int_0^1 \rho(x, t) dx. \quad (4)$$

Φ maybe determined experimentally or theoretically.

Validation through χ -simulations

Simulate a network in χ , consisting of 5 machines, re-entrant with 4 production loops.

Run experiment for different influx levels

Generate average cycle time, average WIP, and average throughput.

Figure 1 shows resulting state equation.




Figure: 1. Seven datapoints for a state equation describing the relationship between cycle time and WIP.

Usage:

1. Determine steady state parameters through inter/extrapolation
2. Use as state equation for transient behavior

Figures 2, 3 show two experiments

1. Transition from a steady state with 75% utilization to 85% utilization with pull policy
2. Transition from a steady state with 67% utilization to 85% utilization with push policy




Figure: 2. Output for a pull policy




Figure: 3. Output for a push policy, zoomed




Figure: 4 Cycle time




Figure: 5 Cycle time

Notice:

Inverse response in Figures 2 and 3

Due to global velocity **model**: Increase in influx leads to a change in total WIP

Result: infinite wave speed and decrease in velocity and hence decrease of output before the increase arrives at the end of the factory.

Reality: re-entrant production has this effect but much less pronounced.

3) Advection diffusion equations

Including variance in stochastic models typically introduces diffusion. We expect that the basic mass conservation model becomes

$$\frac{\partial \rho}{\partial t} + v_{eq} \frac{\partial \rho}{\partial x} = D \frac{\partial^2 \rho}{\partial x^2} \quad (5)$$

$$v_{eq}(t) = \Phi(W(\rho(x, t))) \quad (6)$$

$$W(t) = \int_0^1 \rho(x, t) dx \quad (7)$$

a) Real Factory Data

Data analysis of sanitized data of a real INTEL factory for about 3 months production.

Details:

- ▶ 920 lots
- ▶ time log in and out at all machines
- ▶ identify 8 approximately equally spaced machines
- ▶ Determine time-in at all 8 machines
- ▶ interpolate paths
- ▶ generate histograms at different times.
- ▶ Fit the histograms to the explicit solution of the advection-diffusion equation by a least square fit for the diffusion coefficient.






Figure: 6. Paths of all 920 lots






Figure: 7 Histograms at $t=20, 30$ and 40




Figure: 8. Diffusion coefficient

Result:




Figure: 9 WIP profile after a step up in influx, with and without diffusion

b) χ Simulations - Emiel v.d. Rijt

100 identical machines

characterized through mean process time t_e and squared coefficient of variation c_e^2 .

Arrival process: average interarrival time t_a and its squared coefficient of variation c_a^2

Goal: Determine the dependence of the WIP profile on the ratios

$$\frac{c_a^2}{c_e^2} \quad \text{and} \quad u = \frac{t_e}{t_a}$$

Simulations - Wip profiles:

utilization $u = 0.75$,




Figure: 10 WIP profile for $\frac{c_a^2}{c_e^2} = \frac{1}{9}$




Figure: 15 WIP profile for $\frac{c_a^2}{c_e^2} = \frac{9}{1}$

Boundary layer is utilization dependent: $u = 0.99$

The BL has reduced to one machine.




Figure: 12 WIP profile for $\frac{c_a^2}{c_e^2} = \frac{9}{1}$

PDE model

Consider the steady state of the advection diffusion equation:

$$\rho v_{eq} + D \frac{d\rho}{dx} = \lambda \quad (8)$$

with boundary condition $\rho(0)$ e.g. given by

$$\rho(0) = \frac{1}{2}(c_a^2 + c_e^2) \frac{u^2}{1-u} + u$$

The solution to Eq.(8) is

$$\rho(x) = \frac{\lambda}{v_{eq}} + \left(\rho_0 - \frac{\lambda}{v_{eq}}\right) e^{-\frac{v_{eq}}{D}x} \quad (9)$$

Notice:

with $\rho_{ss} = \frac{\lambda}{v_{eq}}$, e.g.

$$\rho_{ss} = c_e^2 \frac{u^2}{1-u} + u$$

we get that

- ▶ if $c_a^2 > c_e^2$ then $\rho''(x) > 0$,
- ▶ if $c_a^2 < c_e^2$ then $\rho''(x) < 0$,
- ▶ utilization dependence:

Scaling argument: $D \approx \sigma^2$, $\sigma^2 = cv_{eq}^2$

$\lim_{u \rightarrow 1} v_{eq} \rightarrow 0$

Hence from $e^{-\frac{v_{eq}}{D}x}$ the boundary layer ξ becomes $\xi \approx (1-u)$.

4) Factory Master Equation for Linear Factory from First Principles

Goal:

Derive Factory Master Equation from 'First Principles' with methods from gas-dynamics.

General idea:

Boltzmann equation for the density $f(x, y, t)$ of a particle at position x with attribute y at time t :

$$\partial_t f + \partial_x [u(x, y, t)f] + \partial_y (E(x, y, t)f) = Q[f] , \quad (10)$$

$\partial_y (Ef)$ models a continuous change in attribute,

$Q[f]$ models a random and discontinuous change in the attribute

Note that

$$\int Q[f](x, y, t) dy = 0, \quad \forall f . \quad (11)$$

Define part density $\rho(x, t)$ and flux density $F(x, t)$ by

$$\begin{aligned}\rho(x, t) &= \int f(x, y, t) dy, \\ F(x, t) &= \int u(x, y, t) f(x, y, t) dy\end{aligned}$$

integrating we get the conservation law

$$\partial_t \rho + \partial_x F = 0 .$$

as the zero order moment equation.

Goal: Determine E and Q from detailed underlying kinetic behavior and extend to higher moments.

Kinetic density for N particles:

$$f(x, y, t) = \sum_{n=1}^N H(t - a_n) \delta(x - \xi_n(t)) \delta(y - \eta_n(t))$$

$f(x, y, t)$ satisfies the Liouville equation for a single particle density weakly in x :

$$\partial_t f + \partial_x[uf] + \partial_y[Ef] = 0,$$

Boundary condition:

$$f(x = 0, y, t) = \sum_{n=1}^N \delta(y - r_n) \delta(t - a_j),$$

Moment expansion gives the heuristic equation: e.g: assume

$$f(x, y, t) = \rho(x, t) \delta(y - Y(x, t))$$

gives the conservation law with $v(x, t) = u(x, Y(x, t), t)$.

Deriving the state equation

Assume: M stages,
identify the attributes with velocity i.e.

$$u(x, y, t) = y$$

update the velocity every time a particle enters a new stage out of
a probability distribution $P(x, z, t)$ where

$$f(x, y, t) \, dx dy = d\mathcal{P}\{\xi(t) = x, \eta(t) = y\} .$$

defines a probability density to find a particle at position x with
velocity y .

Boltzmann equation

$$\partial_t f + y \partial_x f = M [P(x, y, t) \int z f(x, z, t) \, dz - y f(x, y, t)] \quad (12)$$

Asymptotic expansion for many stages $M \rightarrow \infty$: Chapman-Enskog expansion

$$f(x, y, t) = \phi(\rho(x, t), y, t) .$$

i.e. the kinetic density f is a 'shape function' dependent on space only through the macroscopic density ρ .

Zero order expansion: continuity equation with a state equation

$$v(x, t) = \frac{1}{ME[\tau(x, t)]}$$

$E[\tau]$ denotes the expectation of the cycle time τ under the probability distribution P .

First order expansion - flux becomes:

$$F = \rho v \left(1 + \frac{R}{M}\right) - \frac{1}{M} v V\left[\frac{1}{y}\right] \partial_x \rho . \quad (13)$$

with $V\left[\frac{1}{y}\right]$ the variance of the cycle time.

Equation free model - Kevrekidis et al

Microscopic model: *Monte Carlo simulation*

$$\begin{aligned} (a) \quad & x(t + \Delta t) = x(t) + \frac{\Delta t}{\tau(t)}, \\ & \tau(t + \Delta t) = \kappa(t)\tau(t) + (1 - \kappa(t))\tau(t), \quad t \geq a_n, \\ (b) \quad & \mathcal{P}\{\kappa(t) = 1\} = \omega\Delta t, \quad \mathcal{P}\{\kappa(t) = 0\} = 1 - \omega\Delta t, \\ & d\mathcal{P}\{\tau(t) \leq r\} = \mathcal{I}(r, t)dr, \\ (c) \quad & x(a_n) = 0, \quad d\mathcal{P}\{\tau(a_n) \leq r\} = \mathcal{I}(r, a_n)dr, \end{aligned} \quad (14)$$

microscopic model simulated for 20 short timesteps $\delta t_s = 10^{-3}$
Extract Euler time step for the macroscopic time evolution of the density $\rho(x, t)$.

Coarse time step $\delta t_c = 0.2$

Experiment

Influx:




Figure: 13 Influx




Figure: 15 WIP profile for equation free and PDE simulation




Figure: 15 Outflux for equation free and PDE simulation

5) Open problem: Boundary control of hyperbolic nonlinear wave equations

Consider adiabatic model:

$$\begin{aligned}\frac{\partial \rho}{\partial t} + \frac{\partial F}{\partial x} &= 0 \\ F &= \rho v_{eq}\end{aligned}$$

Optimal control problem: get from one steady state to another in fastest time.

Control parameter: influx at one boundary $\lambda(t)$.

Simplest problem: $v_{eq} = 1$ - linear wave equation.

Solution: Choose $\lambda = \lambda_{new}$.

After $t = 1$ the transition wave will have moved through the interval $[0, 1]$ and we have reached the new steady state

How can this be proven in a way that generalizes to nonlinear and non-local velocities?

Problem: No Pontryagin Maximum principle exists for PDEs.

Attempt: Convert PDE into network of ODEs via semi-discrete methods

Choose: $\Delta x = \frac{1}{n}$

Then

$$\begin{aligned}\dot{x}_1 &= n(\lambda - x_1) \\ \dot{x}_j &= n(x_{j-1} - x_j)\end{aligned}$$

with an initial condition $x_1 = x_j = \lambda_1$

and a final condition $x_1 = x_j = \lambda_{new}$.

and a cost function $C = \int_0^t ds$

Solution due to Pontryagin's maximal principle: find minimum of Hamiltonian

$$H = 1 * \lambda(t) + \sum_j \xi_j(t) x_j(t)$$

with respect to the control parameter. Since H is linear in λ we get *bang-bang* -control:

λ switches between a minimal and maximal value.

Two fundamental problems with this approach:

- ▶ The intuitive result for the PDE suggests that the optimal control parameter is $\lambda = \lambda_{new}$.

How does the ODE bang -bang control approach the PDE?

Weak limit?

There should be theory for that but I can't find any.

- ▶ **Numerical issues:**

Once bang-bang control is established the open problem is to determine the switching manifolds. For n ODEs there will be $n - 1$ switches. How to find those?

Current approach:

Linear optimization problem with nonlinear constraints: Define τ_i to be the time between two switches.

Find

$$\min \sum_j \tau_j$$

subject to the flows $\phi_j(t, x_j)$ which are either explicitly given (linear PDE) or numerically calculated.

Works for up to $n = 9$

not a very good way to numerically check a convergence to a weak limit.

Conclusions

PDE models of production flows are highly effective simulation tools. They can be adjusted to the desired level of accuracy and modeling sophistication. In addition

- ▶ they have execution times in seconds
- ▶ they can be adjusted to include policies
- ▶ they can be adjusted to cover inhomogeneous production lines.
- ▶ they allow to simulate transient situations
- ▶ they can be linked to generate simulations for the whole supply chain
- ▶ they can be justified (in parts) from first principles

Open Problems

- ▶ Find Boltzman equations for queueing networks. Issues:
 - ▶ Gasdynamics: ergodicity assumption in time and space , i.e. strong interactions
 - ▶ Queueing: ergodicity assumption in time and samples, i.e. weak interactions
 - ▶ Queueing networks not well understood - only $M/M/n$ queues lead to good analytical solutions.
- ▶ Use the PDE models to solve business problems, i.e. optimization problems.

References:

- ▶ Dieter Armbruster, Daniel Marthaler, Christian Ringhofer, Karl Kempf, Tae- Chang Jo: A continuum model for a re-entrant factory, in print, Operations research to appear soon (2006)
- ▶ D. Armbruster, C. Ringhofer, Thermalized kinetic and fluid models for reentrant supply chains, SIAM J. on Multiscale modeling and Simulation, **3**(4), pp 782 - 800, (2005)
- ▶ D. Armbruster, P. Degond, C. Ringhofer: A Model for the Dynamics of large Queuing Networks and Supply Chains, SIAM J. Applied Mathematics **66**(3) pp. 896-920. (2006)